



5G / Wi-Fi XR-90 Field Comm Kit



System Specifications:

- Solution Integrated Within A Pelican 1560 Case
 - Overall 22" Long x 18" Wide x 10.5" Tall - 50 lbs.
 - Retractable handle and wheels for easy toting
- Semtech AirLink XR90 Dual 5G Cellular Router
 - Download speeds up to 4.14 Gbps
 - Upload speeds up to 660 Mbps
 - Dual SIM slots
 - Dual 4 x 4 MU MIMO Wi-Fi 6
- Dual Panorama Dome Antennas
 - 5G / Wi-Fi / GPS
 - Wi-Fi effective out to 600' away
- Integrated Gigabit PoE Network Switch
 - 30 watts per port
 - IEEE802.3af/at
- Internal 12 VDC 50-amp hour Life-PO4 rechargeable battery bank
 - Provides for up to 8 hours of operational runtime
- Internal 20-amp LiFe-PO4 battery charger
 - Charger can be enabled when external 120vac is present
- Internal Relay Power Bypass Module
 - Allows kit to operate off of:
 - Internal Battery Power
 - External 120 VAC power source
 - External 12 VDC power source
- Internal Air Circulation System

Specifications Continued:

- Integrated Control Panel For System Operations
- External Panel Mounted Interface Panel
 - Two (2) RJ45 WAN ports
 - Two (2) RJ45 PoE LAN ports
 - One (1) 12 VDC power inlet port
 - Includes 10' long detachable power cord
 - One (1) 120 VAC power inlet port
 - Includes 10' long detachable power cord

SVCI

79 West 4500 South Suite # 1
Murray, UT 84107
801-265-7981 Office
www.svci.us
Email: sales@svci.us